


# 2D Desktop Barcode Scanner XL-2301



- ⊙ Suitable for supermarkets, pharmacies, retail stores
- ⊙ Read all common 1D/2D barcodes from paper labels and electronic screens
- ⊙ 100% own technology to meet customization requirements
- ⊙ A megapixel image ensures better performance in decoding hard-to-read barcodes
- ⊙ Compatible with Linux, Android, Windows XP7/8/10/MAC OS



Model	XL-2301	Cable	Straight 2.0m
Light Source	Red LED (lighting) color temperature 5600K LED	Connector Type	RJ-45 Phone jack connector
CPU	32bit MIPS @1G Hz	Program Upgrade	Online
Scan Mode	Continue scanning & Automatic induction	Input Voltage	DC 5Volts
Image Size	1280x800 pixel	Working Current	130mA
Scanning Speed	60 fps/s	Stand-by Current	100mA
Decoding Depth	0-200mm@(13mil UPC/EAN 100%, PCS=90%)	Drop Durability	Designed to withstand 1M drop
Minimum Resolution	4 mil	Interface	USB-HID, RS-232, USB-VCP
Indicator	(Buzzer), LED (Blue/Red)	Temperature (Operating)	0°C-50°C
Size	L × W × H:150 x 100 x 110mm	Temperature (Storage)	-40°C-70°C
Weight	348g (without cable)	Humidity	5% to 95% (non-condensing)
Case Material	ABS + PC	Light Levels	Daylight, 0-100,00 Lux Fluorescence, 0-5,000 Lux
Decoding Capability	1D: UPC, EAN, Code 39 (with full ASCII), Codabar, Code 128, Code 93, Code 11, Interleaved 2 of 5, Industrial 2 of 5; Matrix 2 of 5, MSI Plessey, GS1 DataBar, etc 2D: PDF417, Data Matrix, QR Code		



**SUNLUX IOT Technology (Guangdong) Inc.**

Office Add: 4F, No.7, Kehui First Street, Science Road, Science City, Guangzhou, China

Tel: +86-20-32053765 Fax: +86-20-82115390 Site: [www.xl-scan.com](http://www.xl-scan.com) E-mail: [sales@xl-scan.com](mailto:sales@xl-scan.com)