

2D Desktop scanner XL-2310



- ⊙ Support USB, PS2, RS-232 interface
- ⊙ Suitable for POS terminals, ticket validators
- ⊙ Wide field-of-view, omni-directional scanning capability
- ⊙ High speed and reliable performance on common codes
- ⊙ Compatible with Linux, Android, Windows XP/7/8/10/MAC OS



Model	XL-2310	Cable	Straight 2.0m
Light Source	Red LED (Lighting) Color Temperature 650nm LED	Mobile tolerance	1m/s
CPU	32bit MIPS @1G Hz	Compatible system	Compatible with Linux, Android, Windows XP/7/8/10/MAC OS
Scan Mode	Continue scanning & Automatic induction	Input Voltage	DC 3.6V-5V
Image Size	1280x800 pix	Working current	< 200mA
Scanning speed	60 fps	stand-by current	< 150mA
Decoding Depth	5~250mm@ (13mil UPC/EAN 100%,PCS=90%)	Indicator	Tone and Volume adjustable
Mnimum Resolution	≥4mil	Interface	USB-HID、USB-VCP、RS-232
Scanning angle	Deflection 360° Inclination ±65° Rotation ±60°	Temperature (Operating)	0°C~50°C
Size	L × W × H:152×152×75(mm)	Temperature (Storage)	-40°C~70°C
Weight	600g	Humidity	5% to 95% (non-condensing)
Case Material	ABS+PC, Flame Retardant Material	Light Levels	0~5000Lux (fluorescence), 0-100,000 Lux (sunlight)
Decoding Capability	1D: UPC,EAN,Code 39 (with full ASCII),Codabar,Code 128,Code 93,Code 11,Interleaved 2 of 5,Industrial 2 of 5,Matrix 2 of 5, MSI Plessy,GS1 DataBar,etc 2D: PDF417,Data Matrix,QR Code,etc		

