

XL-9600

2D Wireless Barcode Scanner



Features

- 1 Buttons support 2 million tests
- 2 Support update online, fast after-sales service
- 3 Storage function, 40,000 EAN-13 barcode support
- 4 Cable Anti - interference design, ensure data transmission
- 5 Super decoding ability, good at reading colored, stained and fuzzy code



Parts Instruction



Logistics Distribution



Warehouse

SUNLUX IOT TECHNOLOGY (GUANGDONG) INC.

Office Add: 4F, No.7, Kehui First Street, Science Road, Guangzhou, China
Tel: +86-20-32053765 Fax: +86-20-82115390
Site: www.xl-scan.com
E-mail: sales@xl-scan.com



XL-9600 Technical Parameters



Performance Parameters	
Image sensor	CMOS
light source	White LED(Lighting) Red LED (Aiming)
CPU	32bit ARM
COMS resolution	640x480 Pixels
Exposure	Global Shutter
Scanning speed	60 fps
Minmum resolution	≥3mil
Decoding depth of field	60-360mm(13mil PCS90%)
Scanning angle	rotate 360°, inclination 65°, elevation 60°
System supported	Android/Windows/Linux/IOS
Scan mode	Manual trigger & Automatic induction
Decoding capability	1DD: Codabar、Code11、Code39、Code32、Interleaved 2 of 5、Industrial 2 of 5、Matrix 2 of 5、Code93、Code128、GS1-128、UPC-A、UPC-E、EAN 8、EAN 13、GS1 DataBar(RSS14)、GS1 DataBar Limited、GS1 DataBar Expanded、etc 2D: PDF417、Micro PDF417、QR Code、Micro QR、Data Matrix、Aztec Code
Physical Parameters	
Size	Scanner: L*W*H= 163*68*80(mm) Charging base: L*W*H=15*6*19(mm)
Weight	Scanner: 175g
Interface	USB
Charging way	Micro USB cable charging
Charging time	4.5H
Standby time	6 months(Dormant state)
Continuous battery life	16H
Battery	Replaceable & Rechargeable lithium battery, 2200mAh
Receiver interface	USB
Material	ABS+TPU
Input voltage	DC 5V
Working current	250mah
Stand-by current	<1uA
Indicator	LED indicator light, buzzer
Interface	USB / USB-VCP
Other Parameters	
Communication methods	2.4G wireless communication, Bluetooth wireless communication
Communication distance	2.4G mode: 100M (open space) Bluetooth mode: 10M (open space)
Temperature (Operating)	-0°C~50°C
Humidity (Operating)	Relative humidity 5%~95%(no condensation)
Temperature (Storage)	-40°C~70°C
Light source	0~5000Lux(fluorescent), 0~100,000Lux(Sunlight)

SUNLUX IOT TECHNOLOGY (GUANGDONG) INC.

Office Add: 4F, No.7, Kehui First Street, Science Road, Guangzhou, China
Tel: +86-20-32053765 Fax: +86-20-82115390
Site: www.xl-scan.com
E-mail: sales@xl-scan.com

